



UMBRELLA COAT



NANO ADDMIX

Build Big.. Add Small...

Umbrella Coat is a white cement based product with redispersible polymer and functional additives for application on interior and exterior rough plasters to give a smooth finish.



PRODUCT BENEFITS

- 2 in 1 Exterior and Interior wall putty
- Water proof composition
- Good Workability
- Vibrant white finish
- Does not require curing with water
- Anti Efflorescence
- Higher Coverage
- Provides smooth and uniform finish to rough plasters
- Good Tensile Adhesion Strength,
- Compressive Strength and Flexural Strength
- Controlled water vapour permeability
- Excellent abrasion resistance
- Resists growth of algae and fungi on wall
- Good intercoat adhesion to emulsion paints

PRODUCT FEATURES

- **AVAILABLE PACKS : 1 kg, 5 kg, & 40 kg**
- **COLOURS AVAILABLE : white**
- **COVERAGE : 2 coats 15 sq.ft/kg for upto 1.5 mm thickness (in 2 coats)**
- **DRYING TIME TO RECOAT : 6-8 hours**
- **RECOMMENDED USAGE : interior and exterior walls**

APPLICATION PROCESS

APPLICATION	THINNER	DILUTION %	APPLICATION VISCOSITY ¹	RECOATING PERIOD
STEP 1 SANDING	SAND THE SURFACE WITH EMERY PAPER 180 AND WIPE CLEAN			
STEP 2 PRE WET THE SURFACE	PRE WET THE SURFACE BEFORE APPLICATION OF 1ST COAT OF UMBRELLA COAT WALL PUTTY			
STEP 3 FIRST UMBRELLA COAT KNIFE / TROWEL	WATER	40% - 50%	N/A	6 - 8 HRS
STEP 4 SECOND UMBRELLA COAT WALL PUTTY	WATER	40% - 50%	N/A	6 - 8 HRS
STEP 5 PRIMER AND EMULSION COAT	APPLY A COAT OF PRIMER FOLLOWED BY 2 - 3 COATS OF EMULSION			



UMBRELLA COAT



NANO ADDMIX
Build Big.. Add Small...

Umberalla Coat

वॉल पुट्टी जल रोधक (Water Repellent) व्हाईट-सिमेंट आधारित पुट्टी है । Umbrella Coat में विभिन्न पॉलीमर व रसायन से युक्त है । जिससे यह उत्पाद अंदरूनी व बाहरी दोनों, खुरदरे प्लास्टर (Rough Plaster) पर बहुत ही चिकना परिसञ्जन (Smooth Finish) देता है ।



PRODUCT BENEFITS (उत्पाद लाभ)

- 2 in 1 : अंदरूनी व बाहरी दिवार के लिए उपयुक्त
- जल रोधक रचना
- अच्छी कार्यशीलता
- जीवंत सफेद फिनिश
- अच्छा कवरेज-कम लागत
- चिकनी एवं एक समान फिनिश
- अच्छी एवं मजबूत पकड
- दिवार पर शैवाल और कवक से विकास को रोके
- इमल्शन पेंटस् पर बढिया इंटरकोट आसंजन



पैकिंग : १ कि.ग्रा., ५ कि.ग्रा. व ४० कि.ग्रा.,

कलर : सफेद

कवरेज : १५ स्क्वैर फूट प्रति किलो : २ कोट : १.५ मि.मी. परत के लिए (प्रति कोट ६-८ घंटे के अंतराल में लगाए)

अनुरांसित उपयोग : अंदरूनी व बाहरी दिवारों के लिए उपयुक्त

