

TOUGH SEAL37

(2 Component – Epoxy Grout System)

TOUGH SEAL37 is Two Component Epoxy Grout and adhesive, suitable for Tile Joints between 0 to 10 mm. guarantees High Bonding and Long - lasting performance in tile joints.

Application :

- Suitable for Internal Floors and Walls
- Suitable for Ceramic, Vitrified tiles, Large format tiles
-

Benefits :

- Excellent adhesion, bear good mechanical strength
- Uniform & smooth application
- High colour value
- Water proof, Stain proof
- Can be easily cleaned in wet conditions
- Long lasting performance

Application Guide :

- Clean the application area properly, make sure its dust & oil free
- Mix properly **TOUGH SEAL37** : Product A & B with mechanical stirrer
- Fill **TOUGH SEAL37** using a hard rubber or a flexible metal trowel with good pressure
- Remove excess material immediately with a sponge or plain cloth
- Adding 10% Alcohol in wash water is recommended for better condition in wet condition
- If drying is complete, the sealant can be cleaned with **KLAINI 11**
- At Room Temperature, application time is about 30 minutes

PACKING :

1 KG & 5 KG (On demand)

	1 Kg pack	5 Kg pack
COMPONENT A	0.940 Kg	4.700 Kg
COMPONENT B	0.060 Kg	0.300 Kg

Shelf Life :

12 months from the manufacturing dates

Disclaimer:

The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests and take trials to ensure on suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of the other materials used and on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The Company does not assume any liability or any consequential damage for unsatisfactory results, arising from the use of our products.