

RAPID BOND

Features & Benefits :

- High Strength & Flexible
- Easy to use
- Can handle any kind mild shocks
- Works in all weather conditions
- Suitable for both Interior & Exterior building areas
- Can be used on any size / shape of Tile on Tile / Stone on Stone application

Precautions for application and storage :

- The ratio of Component A & Component B should be 1 : 0.5 by weight.
- Use of an electronic weighing scale is must
- Use of blender / stirrer to mix Component A & B is strongly recommended
- Keep containers tightly closed in cool shaded place
- While application use Hand gloves and goggles
- If contact with eye, rinse thoroughly and seek medical treatment

Packing :

- 0.9 kg, 1.8 kg

	0.9 kg Pack	1.8 kg Pack
Component A	0.5 kg	1.0 kg
Component B	0.4 kg	0.8 kg
Total	0.9 kg	1.8 kg



Physical Properties :

S.No	Test Conducted	Average Results
1	Tensile Adhesion (N/mm ²)	
	a) Dry Condition	1.65
	b) Wet Condition	1.44
2	Shear Adhesion (N/mm ²)	
	a) Dry Condition	4.25
	b) Heat Ageing	4.62
	c) Wet Condition	4.16
3	Open Time (Minutes)	50
4	Adjustability	60
5	Slip (mm)	0.1
6	Deformability (mm)	> 5